

Lensagon CVM0411ND

4.4mm~11mm F1.6 For 1/1.8" format cameras Megapixel suitable C-mount

| MODEL NUMBER | | Lensagon CVM0411ND | | | |
|-----------------------------|-------|---------------------|----------|-----------|--------|
| MOUNT | | С | | | |
| IMAGE FORMAT | | 1/1.8" | | | |
| FOCAL LENGTH | | 4.4~11mm | | | |
| MAXIMUM APERTURE | | F1.6 | | | |
| IRIS RANGE | | F1.6~F16 | | | |
| IMAGE SIZE | | Ø9 5.4x7.2mm | | | |
| BACK FOCAL LENGTH | | W8.75 T14.48 in air | | | |
| FLANGE FOCAL LENGTH | | 17.526mm | | | |
| MINIMUM WORKING DISTANCE | | 0.3m | | | |
| FIELD OF VIEW | VER. | W61.2° | T28.0° | ½" W55.5° | T25.0° |
| | HOR. | 76.6° | 36.7° | 70.1° | 32.9° |
| | DIA. | 89.4° | 44.8° | 82.5° | 40.4° |
| LENS CONSTRUCTION | | 7 Groups 9 Elements | | | |
| CLEAR APERTURE | FRONT | Ø30.0 | | | |
| | REAR | Ø8.0 | | | |
| EXIT PUPIL POSITION | | W-61.4m | T-22.3mm | | |
| FILTER SIZE | | M43mm P=0.75 | | | |
| DISTORTION | | W-0.2% | T0.35% | ½" W-0.1% | T0.26% |
| WEIGHT | | g | | | |
| OPERATING TEMPERATURE RANGE | | -10° ~ 50° | | | |

DIMENSION

